APC Back-UPS[™] 800, 1100



Part Number: BX800LI, BX1100LI

Battery Backup with Surge Protection for Computers and Electronics

The Back-UPS 800 and 1100 from APC by Schneider Electric protect your computer and electronic equipment from damaging power outages, surges and spikes while providing short term battery power during an outage. The 800 and 1100 feature Automatic Voltage Regulation (AVR), which instantly adjusts high and low voltage fluctuations to safe levels for your electronics, saving battery power for when you need it most during storms and power outages. Equipped with IEC sockets, the BX800LI and BX1100LI keep your desktop computer, monitor or other critical devices (router, modem, television, etc.) running when the power goes out. Specifically designed to protect electronic equipment in harsh power environments, the Back-UPS 800 and 1100 ensure maximum productivity and work efficiency.



BX800LI



BX1100LI

Product Features

LED Indicator and Audible Alarms
Quickly understand the unit and power status through
visual and audible indicators.

2 Automatic Voltage Regulation (AVR)

"Boost and Trim" AVR instantly corrects voltage fluctuations without using the battery, allowing you to work indefinitely through inconsistent power, saving battery life for outages.

4 to 6 IEC Battery Backup and Surge Protected Sockets Keep critical electronic equipment running when the power goes out, so you can protect your work and save your data.

4 Push Button Circuit Breaker

Provides for easy recovery from circuit overloads and protects your UPS and connected electronics from electrical damage.

5 Automatic Diagnostic Testing

Periodic battery self-test ensures early detection of a battery that needs to be replaced, ensuring your unit is ready when you need it.

6 2 Yr Warranty

APC offers a 2 year warranty with free technical phone and online support, providing customer peace of mind.

Easy to use "one step" battery connector.



Back-UPS BX800LI, BX1100LI Specifications

Model Number	BX800LI	BX1100LI
Output		
Output Capacity	800 VA / 415 Watts	1100 VA / 550 Watts
Output Voltage / Frequency (On utility)	230V, 50/60 +/-3 Hz	
Output Voltage / Frequency (On battery)	230V, 50 or 60 Hz +/-1 Hz (auto-sensing)	
Output Connections	4 IEC 320 C13 sockets	6 IEC 320 C13 sockets
Waveform Type	Stepped Approximation to Sine Wave	
Input		
Input Voltage / Frequency	140 – 300 V, 50/60Hz +/-3Hz	150 – 280 V, 50/60Hz +/-3Hz
Input Connection	IEC-320 C14	
Surge Protection		
AC Power Surge Protection	All sockets	
Physical		
Unit Dimensions (H x W x D)	199 x 115 x 256 mm	215 x 130 x 336 mm
Unit Weight	6.2 Kg	8.8 Kg
Shipping Dimensions (H x W x D)	290 x 205 x 345 mm	295 x 245 x 440 mm
Shipping Weight	6.5 Kg	9.8 Kg
Color	Black	
UPC Code	731304315179	731304315155
Battery		
Battery Type	Maintenance-free, sealed lead-acid battery, leak proof	
Battery Size	12 volt, 7.Ah	12 volt, 9 Ah
Management		
Alarms	Visual (LED) and audible alarms	
Adjustable Sensitivity and Transfer Voltage	Low, Medium (default), High	
Conformance		
Warranty	1 year repair or replace (excluding battery) and 1 year for battery	
Regulatory Approvals	CE, EAC	

APC by Schneider Electric

Contact: 59 41 22 26

